

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Mabanol Radon Gear ATF DCT

Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC24 Lubricants, greases, release products

Process category

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC20 Heat and pressure transfer fluids in dispersive, professional use but closed systems

Environmental release category

ERC4 Industrial use of processing aids in processes and products, not becoming part of articles
ERC7 Industrial use of substances in closed systems
ERC9a Wide dispersive indoor use of substances in closed systems
ERC9b Wide dispersive outdoor use of substances in closed systems

Application of the substance / the mixture Transmission oil

1.3 Details of the supplier of the safety data sheet

Company name: Mabanol GmbH & Co. KG
Street: Admiralitätstraße 55
Place: D-20459 Hamburg

Further information obtainable from:

Telephone: +49 (0) 40 36809988

Emergency telephone number: Giftinformationszentrale Göttingen

Telephone: 0551/1 92 40

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3
H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms Void

Signal word Void

Hazard statements

H412 Harmful to aquatic life with long lasting effects..

Precautionary statements

P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains Ethanol, 2,2'-iminobis-, N-tallow alkylderivs., 2-ethylhexyl methacrylate, C14-18 alpha-olefin epoxide, reaction products with boric acid. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:

CAS: 72623-86-0 EINECS: 276-737-9 Reg.nr.: 01-2119474878-16	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based ⚠ Asp. Tox. 1, H304	25-50%
CAS: 68784-17-8 EINECS: 272-225-4 Reg.nr.: 01-2119960832-33	Isooctadecanoic acid, reaction products with tetraethylenepentamine ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-2,5%
CAS: 36878-20-3 EINECS: 253-249-4 Reg.nr.: 01-2119488911-28	bis(nonylphenyl)amine Aquatic Chronic 4, H413	1-2,5%
CAS: 91648-65-6 EINECS: 293-927-7 Reg.nr.: 01-2119976351-35	substituted thiadiazol Aquatic Chronic 3, H412	1-2,5%
CAS: 61791-44-4 EINECS: 263-177-5	Ethanol, 2,2'-iminobis-, N-tallow alkylderivs. ⚠ Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	0,1-1,0%
CAS: 688-84-6 EINECS: 211-708-6 Reg.nr.: 01-2119490166-35	2-ethylhexyl methacrylate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	0,1-1,0%
CAS: 122-39-4 EINECS: 204-539-4	Diphenylamin ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT RE 2, H373; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0,1-1,0%
	C14-18 alpha-olefin epoxide, reaction products with boric acid ⚠ Skin Sens. 1B, H317	0,1-1,0%

Additional information:

* Contains one or more of the following CAS-numbers: 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-65-0, 64742-71-8, 68037-01-4, 72623-83-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 8042-47-5, 848301-69-9.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, dry chemical, or foam. Water can be used to cool and protect exposed material.

For safety reasons unsuitable extinguishing agents:

Wasser im Vollstrahl

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Remove from the water surface (e.g. skim or suck off).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Avoid the formation of oil haze.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

122-39-4 Diphenylamin

WEL Short-term value: 20 mg/m. Long-term value: 10 mg/m.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Respiratory protection: Not required.

Protection of hands



Wear gloves for the protection against chemicals according

Oil resistant gloves

Material of gloves

Nitrile rubber, NBR, PVC gloves, Neoprene gloves

Recommended thickness of the material: > 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Goggles recommended during refilling

Body protection:: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Clear
Odour:	Characteristi

Change in condition

Boiling point/Boiling range: Undetermined.

Drip point:

Pour point -48 °C (ASTM D97)

Flash point:

> 201 °C

Flammability (solid, gaseous):

Not applicable

Self-igniting:

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined.

Upper: Not determined.

Density at 20 °C:

0,854 g/cm³

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Kinematic at 40 °C:	34 mm ² /s
100 °C	7,0 mm ² /s (ASTM D445)
Solvent content: Organic solvents:	0,0 %
<u>9.2 Other information</u>	No further relevant information available

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 2000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 (4 h)	> 5,53 mg/l (rat) (OECD 403)
122-39-4 Diphenylamin		
Oral	LD50	1120 mg/kg (rat)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50 (4 h)	3 mg/l (ATE)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Sensitisation For respiratory and skin sensitisation: Not expected to be a sensitiser.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Mabanol Radon Gear ATF DCT

72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
LL/EL/IL50	>100 mg/l (fish)
122-39-4 Diphenylamin	
LC50 (48 h)	>1100 mg/l (fish)

12.2 Persistence and degradability No further relevant information available

12.3 Bioaccumulative potential No further relevant information available

12.4 Mobility in soil No further relevant information available

Ecotoxicological effects:

Remark: Harmful to fish

Remark: This material is expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Additional ecological information:

General notes: Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage System.

European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN- Number

ADR, ADN, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, ADN, IMDG, IATA

Klasse Void

14.4 Packing group

ADR, ADN, IMDG, IATA Void

14.5 Environmental hazards::

Marine pollutant: No

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable.

UN "Model Regulation":

Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H290 May be corrosive to metals.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr. 1: Corrosive to metals, Hazard Category 1

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

Sources EC/453-2010

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)
