

Mabanol Radon Gear ATF VI

High Performance Automatic Transmission Fluid

Application

Mabanol Radon Gear ATF VI is a high-performance automatic transmission fluid which is suitable for modern automatic transmissions and hydraulic steering systems in passenger cars and commercial vehicles. The product complies with the latest GM specification Dexron VI as well as former DEXRON specifications IIG, IIIG, IIIE etc. and it is backward compatible and can be used where products according to GM Type A, Suffix A (TASA) are required.

Properties

Mabanol Radon Gear ATF VI is formulated using high-selected base stocks and additive package based on modern synthetic technology. The automatic transmission fluid offers outstanding performance and stability of the friction coefficient as well as optimal shifting under all operating conditions. Furthermore it guarantees a very good wear, corrosion and oxidation protection for reliable operation and longest lifetime. Mabanol Radon Gear ATF VI is dyed red.

Specifications

- GM ATF Dexron VI
- Ford Mercon LV

Approved under a different title / recommended for

- Aisin Warner JWS 3309/JWS 3324AW-1
- Isuzu BESCO ATF-II/ATF-III
- Saab T-IV (JWS 3309)/93 165 147
- Allison C-3/C-4
- Jaguar ATF 3403 M115/JLM 20238/ LT 71141/ ZF 5HP 24
- Audi 5 HP LT 71141/G 052 162-A1/A2/G 055 025 A2

- Scion (All Vehicles)
- Jeep ATF+3/+4
- Subaru ATF/5AT/HP
- BMW JWS 3309/LA 2634/LT 71141/7045E/ETL 8072B/ZF 5HP18FL/5HP24/5HP30/BMW Mini
- Kia SP-II/SP-III/SP-IV/SP-IVM/Red 1
- Suzuki ATF 2326/2384 K/ 3309/3314/3317
- Mazda ATF D-II/M-III/M-V/FZ/F-1/S-1/N-1
- Toyota ATF D-II/D-III/ATF T-III/T-IV/WS
- MB-Sheet 236.1/236.2/236.3/236.5/236.6/236.7/236.8/236.9
- Caterpillar TO-2
- Vickers M2950-S/I-286-S
- Chrysler ATF+/-2/+3/+4
- Mini Cooper T-IV
- Voith 55.6336.XX
- Daewoo LT71141
- Mitsubishi Diaqueen SK/SP-II/SP-III/Diaqueen SP-IV/AW/J2/J3
- Volvo CE 97340
- Fiat T-IV type/JWS 3309
- VW 5 HP (ZF 5 HP 30)/5HP (18FL, 30)/5HP (19FL, 24A)/G-055-025-A2/TL 521 61
- Ford Mercon FNR5/M2C138-CJ/M2C166-H/WSS M2C 922 A1/924 A (XT-8-QAW)
- Nissan Matic Fluid C/D/J/K/S
- Peugeot ZF 4HP20
- Porsche ZF 5HP19FL/ZF 5HP20/ATF 3403 M115/LT 71141/T-IV (JWS 3309)
- Hyundai/KIA SP-IV-M/SP-IV-RR
- Hyundai SP-III/Dex-II/SP-II
- ZF 3&4 Speed Transmissions
- ZF TE-ML 09/11A/11B

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,845
Dyn. Viscosity at -30°C	DIN 51 398	mPa s	10.000
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	27,6
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	5,66
Viscosity Index (VI)	DIN ISO 2909		151
Flash point COC	DIN ISO 2592	°C	208
Pourpoint	DIN ISO 3016	°C	-51

Updated in April 2017

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987