

Mabanol Xenon Alpha C4 5W-30

Synthetic High Performance Engine Oil

Application

Mabanol Xenon Alpha C4 5W-30 is high-performance low friction oil using a Low SAPS formulation. It is produced with a special blend of synthetic components and a high-quality additive package.

The very good low temperature properties enable a smooth engine cold start. Severe and heavy loads are handled under all operating conditions and the high temperature performance is excellent. It boasts improved wear protection and friction losses are significantly reduced (HTHS < 3,5 mPas).

Properties

Mabanol Xenon Alpha C4 5W-30 is specially developed for passenger cars with Diesel Particulate Filters, most notably the Renault / Dacia Group, where ACEA C4 standards are required. The fuel economy formulation and reduced engine stress has a positive effect on the life cycle of the Diesel Particulate Filter.

Specifications

- SAE Grade 5W-30
- ACEA C4

Approved under a different title / recommended for

- Renault RN 0720
- MB-Sheet 226.51

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,851
Dyn. Viscosity at -30°C	ASTM D 5293	mPa s	5.990
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	69,2
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	12,1
Viscosity Index (VI)	DIN ISO 2909		174
Flash point COC	DIN ISO 2592	°C	232
Pourpoint	DIN ISO 3016	°C	-42
Total base number	DIN ISO 3771	mgKOH/g	7,1
Sulphated ash	DIN 51 575	g/100 g	0,48

Updated in August 2016

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981