

# Mabanol Xenon Alpha Stellar 5W-40

## Partly Synthetic High Performance Engine Oil

### Application

Mabanol Xenon Alpha Stellar 5W-40 is a high-performance low-friction engine oil designed for use in petrol and diesel engines including turbocharged and direct injection engines under all operating conditions.

Mabanol Xenon Alpha Stellar 5W-40 is suited to be used in Mercedes Benz engines requiring 229.5 also covering various Maybach and AMG makes (manufacturer's recommendations have to be followed at all times). The product is backward-compatible to MB-Sheet 229.3.

### Properties

Mabanol Xenon Alpha Stellar 5W-40 is a high-performance low-friction motor oil of the viscosity grade SAE 5W-40. Synthetic components and innovative additives combined ensure that the demands of the latest OEM standards are fully met. Improved anti-wear and engine cleanliness are ensured even for the latest extended oil drain intervals.

Mabanol Xenon Alpha Stellar 5W-40 also excels in providing fantastic cold temperature properties and distinguishes itself even during extremely low ambient temperatures.

### Specifications

- SAE Grade 5W-40
- ACEA A3/B4
- API SN/CF
- JASO MA

### Approvals

- MB-Approval 229.5
- VW-Norm 502 00/505 00

### Approved under a different title / recommended for

- MB-Sheet 226.5
- BMW Longlife-01
- VW-Norm 501 01
- Porsche A40
- Opel GM-LL-B-025
- Renault RN 0700/ RN 0710
- PSA B71 2296

### Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,853
Dyn. Viscosity at -30°C	ASTM D 5293	mPa s	6.100
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	87,1
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	14,3
Viscosity Index (VI)	DIN ISO 2909		171
Flash point COC	DIN ISO 2592	°C	238
Pourpoint	DIN ISO 3016	°C	-42
Total base number	DIN ISO 3771	Mg KOH/g	10,7
Sulphated ash	DIN 51 575	g/100g	1,3

Stand: August 2016

Die angegebenen Werte können im handelsüblichen Rahmen schwanken.

Zolltarifnummer: 2710 1981