

Mabanol Xenon Alpha Classic 20W-50

High Performance Universal Engine Oil

Application

Mabanol Xenon Alpha Classic 20W-50 is designed for year-round use in passenger car engines.

The performance ability of this universal engine oil corresponds to the manufacturer's demands for petrol and diesel fuelled vehicles with or without turbochargers.

Properties

Mabanol Xenon Alpha Classic 20W-50 meets the standards of SAE grade 20W-50. The viscosity formulation provides excellent lubricating properties at high outside temperatures and is perfectly suitable for engines with a high mileage performance.

Specifications

- SAE Grade 20W-50
- ACEA A3/B4
- API SL/CG-4

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,888
Dyn. Viscosity at -15°C	ASTM D 5293	mPa s	9.070
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	157
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	17,5
Viscosity Index (VI)	DIN ISO 2909		122
Flash point COC	DIN ISO 2592	°C	240
Pourpoint	DIN ISO 3016	°C	-33
Total base number	DIN ISO 3771	mgKOH/g	8,8
Sulphated ash	DIN 51 575	g/100 g	1,15

Updated in August 2016

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981