

Mabanol Radon Gear ATF III MV

High Performance Automatic Transmission Fluid

Application

Mabanol Radon Gear ATF III MV is an automatic transmission fluid which complies with Ford Mercon V as well as the General Motors standards Dexron. It can be equally used in automatic transmissions of passenger cars and heavy-duty vehicles as well as in steering systems. It can also be used in lock-up clutches.

Properties

Mabanol Radon Gear ATF III MV offers protection against wear, corrosion, friction and oxidation. Those properties are featured thanks to the formulation of carefully selected base oils including synthetic components and the most suitable additive package.

The transmission fluid is backward compatible to a wide range of MAN specifications (Type 339 V1 / Z1 amongst others) and is also well suited to Mercedes Benz applications (fully covering numerous standards such as 236.9, 236.10, 236.11, 236.12, 236.14, 236.15, 236.41, 236.81 or 236.91).

Mabanol Radon Gear ATF III MV is neither to be used in Dual Clutch Transmissions (DCT / DSG) nor in Continuously Variable Transmissions (CVT). The product is dyed red.

Approvals

- MAN 339 Typ V2/Z2
- MAN 339 Typ Z 11
- MB-Approval 236.6

Approved under a different title / recommended for

- Ford Mercon V
- Aisin Warner JWS 3309
- Allison TES-295/-389/Allison C-4
- BMW 7045E/8072B/LA 2634/LT 71141
- Chrysler ATF +3/+4/MOPAR ASRC
- GM DEXRON IIIH/IIIG/IID
- Hyundai/KIA SP-II/SP-III/JWS 3314/JWS 3317
- Honda ATF Z-1
- Idemitsu K17 (JATCO)
- Isuzu NPR ECO MAX/NPR HD/NPR XD/NQR und NRR-SCS
- KIA Red-1
- MB-Sheet 236.14/236.15/236.41/236.81/236.91
- Mazda ATF-M III/ATF-MV
- Mitsubishi Diaqueen ATF J3/SP-II/SP-III
- Nissan 402/Nissan Matic-D, J, K
- Voith H55.6335 (G 607)/H55.6336
- PSA AL-4
- Renault DP-0
- Saab 3309
- Suzuki 3314/3317
- Subaru ATF/ATF-HP
- Toyota T/T-II/T-III/T-IV
- Volvo 97340/97341/speed (P/N 1161621)/ (PIN 1161540)
- VW G 052 162/G 052 990/G 055 025/G 055 005/G 055 162/G 052 540
- ZF TE-ML 03D/04D/05L/09/11A/11B/14A/14B/16L/17C/20B/21L

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,851
Dyn. Viscosity at -40°C	DIN 51 398	mPa s	< 20.000
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	36,0
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	7,49
Viscosity Index (VI)	DIN ISO 2909		182
Flash Point COC	DIN ISO 2592	°C	210
Pourpoint	DIN ISO 3016	°C	-54

Updated in April 2017

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987