

Mabanol Radon Gear ATF CVT

Multi-Purpose Fluid for Continuously Variable Transmissions

Application

Mabanol Radon Gear ATF CVT is an automatic transmission fluid perfectly suited to continuously variable transmissions. It can be equally used for CVT versions equipped with pushbelts.

Properties

Mabanol Radon Gear ATF CVT's formulation is a blend of high-quality base stocks and a matching additive package. To ensure a reliable operation, longer durability and low friction, the product offers a very good wear, corrosion and oxidation protection.

The product is not suitable for use in hybrid CVTs (Honda/Ford), DCTs (Dual Clutch Transmission) or automatic stages.

Mabanol Radon Gear ATF CVT is dyed red.

Recommended for

- Toyota CVTF TC/ CVTF FE
- Nissan NS-1/NS-2/NS-3/CVTF NS II
- Honda HMMF/HCF2
- Mitsubishi SP-III/CVTF-J1
- Subaru CV-30/CVTF-II/High Torque CVTF
- Subaru ECVT/iCVT
- Daihatsu Ammix CVT
- Suzuki CVTF TC/NS-2/CVT Green 1
- MB-Sheet 236.20
- Hyundai SP-III
- Chrysler Jeep NS-2
- Mini Cooper EZL799
- VW TL 052 180/TL 052 516

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,848
Dyn. Viscosity at -30°C	DIN 51 398	mPa s	8.500
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	32,6
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	6,99
Viscosity Index (VI)	DIN ISO 2909	-	183
Flash point COC	DIN EN ISO 2592	°C	212
Pourpoint	DIN ISO 3016	°C	-48

Updated in Juni 2017

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987