

# Mabanol Delta 2T-R

## Semi-Synthetic Two Stroke Engine Oil

### Application

Mabanol Delta 2T-R is recommended in accordance with manufacturer's instructions for mixing ratios of up to 1:50 and for separate lubrication (autolube systems). This two-stroke engine oil complies with the highest specifications for both the Asian and the European market.

### Properties

Mabanol Delta 2T-R is a self-mixing semi-synthetic low-smoke two-stroke motor oil. Mineral oils derived from the most modern refinery techniques, synthetic components and special additives guarantee optimal lubricity and a high degree of engine cleanliness. Deposit build-up in the combustion chamber and the exhaust system are prevented, smoke development is substantially reduced.

### Specifications

- ISO L-EGD
- API TC
- JASO FC
- TISI

### Approved under different title / recommended for

- Husqvarna Chainsaw

### Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,872
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	67,5
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	9,53
Viscosity Index (VI)	DIN ISO 2909		121
Flash point PM	DIN ISO 2592	°C	123
Pourpoint	DIN ISO 3016	°C	-33
Total base number	DIN ISO 3771	mg KOH/g	1,1
Sulphated ash	DIN 51 575	g/100g	0,05

Updated in August 2016

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981